

## Gallons Per Hour Pump Performance Comparison Chart

Foot Lift	1	5	10	15	20	24
MARS	125	98	74	70	43	7
Comp. 1	84	75	60	42	10	0
Comp. 2	117	98	70	58	11	0
Comp. 3	105	95	73	36	0	0

A	Feature	MARS	Comp.	Comp.	Comp.
	24 ft. Lift	•			
	Motor Corrosion Protection	•			
	Drip Proof Motor Housing	•	•		•
	Drip Proof Motor & Switches	•			
l	Vibration Absorbing Rubber Feet	•	•	•	
	Side Mount	•	•	•	•
	Quick Release Check Valve	•	•		
	Internal Safety Switch	•		•	
	Solid Float	•	•		•

Features:	MARS #	Description		
☐ 24 Foot Lift ☐ Class Leading Performance	21780	115 V, 60 Hz, 0.91 Amps, 71 Watts 6' Cord, 3/8" Check Valve, Safety Switch Medium Reservoir		
☐ Quiet Operation ☐ Compact Design	21781	115 V, 60 Hz, 0.91 Amps, 71 Watts 6' Cord, 3/8" Check Valve, Safety Switch 20' Tubing, Medium Reservoir		
<ul><li>☐ Quick Clean/Quick Release</li><li>☐ Duck Bill Check Valve</li><li>☐ Integrated Safety Switch</li></ul>	21782	230 V, 60 Hz, 0.6 Amps, 75 Watts 6' Cord, 3/8" Check Valve, Safety Switch Medium Reservoir		
□ Rubber Isolation Feet □ Patent Pending Design  □ WARNING: Cancer and Reproductive Harm www.P65Warnings.ca.gov	21783	230 V, 60 Hz, 0.6 Amps, 75 Watts 6' Cord, 3/8" Check Valve, Safety Switch 20' Tubing, Medium Reservoir		